



# DC Axial Fan

## AT1225L Series

120x120x25mm I



Model	Rated Voltage (VDC)	Operating Voltage (VDC)	Rated Current (AMP)	Power Consumption (WATTS)	Speed Reference (RPM)	AirFlow		Static Pressure		Acoustic Noise (dBA)
						(CMM)	(CFM)	(mm-H <sub>2</sub> O)	(Inch-H <sub>2</sub> O)	
AT1225L-12TLS/2B/FB(-)	12	8~13.8	0.07	0.84	1200	1.436	50.72	0.98	0.039	23.9
AT1225L-12LLS/2B/FB(-)	12	8~13.8	0.14	1.68	1600	1.898	67.01	1.63	0.064	31.4
AT1225L-12LS/2B/FB(-)	12	8~13.8	0.27	3.24	2000	2.425	85.64	2.43	0.096	37.2
AT1225L-12MS/2B/FB-	12	8~13.8	0.37	4.44	2400	2.940	103.82	3.50	0.138	42.5
AT1225L-12HS/2B/FB-	12	8~13.8	0.68	8.16	2800	3.395	119.90	4.93	0.194	47.5
AT1225L-12HH2B-	12	8~13.8	1.14	13.68	3200	4.125	145.69	6.17	0.243	51.4
AT1225L-24LS/2B/FB-	24	12~27.6	0.17	4.08	2000	2.425	85.64	2.43	0.096	37.2
AT1225L-24MS/2B/FB-	24	12~27.6	0.20	4.80	2400	2.940	103.82	3.50	0.138	42.5
AT1225L-24HS/2B/FB-	24	12~27.6	0.31	7.44	2800	3.395	119.90	4.93	0.194	47.5
AT1225L-48LS/2B/FB-	48	24~52.8	0.10	4.80	2000	2.425	85.64	2.43	0.096	37.2
AT1225L-48MS/2B/FB-	48	24~52.8	0.13	6.24	2400	2.940	103.82	3.50	0.138	42.5
AT1225L-48HS/2B/FB-	48	24~52.8	0.22	10.56	2800	3.395	119.90	4.93	0.194	47.5



DC Fan

## DC FAN

- Frame & Impeller: Plastic (UL94V-0)
- Bearing: Dual Ball Bearing
- Basic Locked Roter and Polarity Protected
- Safety Standards: UL/CUL, TUV