



DC Diagonal Fan

AT7010L Series

70x70x10.8mm



| Model | Rated Voltage (VDC) | Operating Voltage (VDC) | Rated Current (AMP) | Power Consumption (WATTS) | Speed Reference (RPM) | AirFlow (CMM) (CFM) | Static Pressure (mm-H ₂ O) (Inch-H ₂ O) | Acoustic Noise (dBA) |
|----------------------------|---------------------|-------------------------|---------------------|---------------------------|-----------------------|---------------------|---|----------------------|
| AT7010L-12LS/2B/1B/FB □□X | 12 | 9~13.8 | 0.04 | 0.48 | 1500 | 0.098 3.45 | 2.14 0.084 | 23.1 |
| AT7010L-12MS/2B/1B/FB □□X | 12 | 6~13.8 | 0.10 | 1.20 | 2000 | 0.168 5.95 | 4.45 0.175 | 24.0 |
| AT7010L-12HS/2B/1B/FB □□X | 12 | 6~13.8 | 0.14 | 1.68 | 2500 | 0.193 6.82 | 8.00 0.315 | 28.8 |
| AT7010L-12HHS/2B/1B/FB □□X | 12 | 6~13.8 | 0.15 | 1.80 | 3000 | 0.207 7.32 | 11.30 0.445 | 32.6 |
| AT7010L-12TH2B/1B-□□X | 12 | 6~13.8 | 0.25 | 3.00 | 3500 | 0.252 8.88 | 14.96 0.589 | 36.7 |



DC FAN

- Frame & Impeller: Plastic (UL94V-0)
- Bearing: Dual Ball Bearing
- Basic Locked Roter and Polarity Protected
- Safety Standards: UL/CUL, TUV