

DIMENSION	VDC					BEARING				OPTIONAL DEVICE								SAFETY			WEIGHT		
mm	3.3V	5V	12V	24V	48V	(S) SLEEVE	(1B) 1B&1S	(2B) 2 BALLS	(FB) LONG LIFE	(NF) TACHO OUTPUT	AUTO RESTART PROTECTION				(T) TEMP. SENSOR	(M) PWM	(W) IP22	(X) IP54	(Y) IP55	UL/ CUL	TUV	CE	g
											(PD) NO SIGNAL	(PF) FG SIGNAL	(PH) ALARM HIGH	(PL) ALARM LOW									
ATX SERIES DC DIAGONAL FAN																							
40x40x08		V	V			V		V	V	V	V	V	V			V	V		V	V	V	7	
45x45x10		V	V			V		V	V	V	V	V	V			V	V		V	V	V	19	
50x50x10IV		V	V					V		V	V	V	V			V	V		V	V	V	9	
60x60x10II		V	V			V		V	V	V	V	V	V			V	V		V	V	V	13	
70x70x10II		V	V			V		V	V	V	V	V	V			V	V		V	V	V	16	
ATB SERIES DC BLOWER																							
B50x50x15		V	V	V				V		V	V	V	V			V	V		V	V	V	24	
B60x60x10I		V	V	V				V		V	V	V	V			V	V		V	V	V	20	
B60x60x10II		V	V	V		V		V	V	V	V	V	V			V	V		V	V	V	23.4	
B60x60x15II		V	V					V		V	V	V	V			V	V		V	V	V	28	
B60x60x25			V	V	V			V		V	V	V	V			V	V					52	
B70x70x20		V	V	V		V			V	V	V	V	V			V	V		V	V	V	32	
B75x75x30			V	V	V			V		V	V	V	V	V	V	V	V	V	V	V	V	61	
B92x92x25II			V	V		V			V	V	V	V	V			V	V		V	V	V	58	
B97x97x33			V	V	V			V		V	V	V	V	V	V	V	V		V	V	V	142	
B120x120x25			V	V		V			V	V	V	V	V			V	V		V	V	V	79	
B120x120x32			V	V	V			V		V	V	V	V	V	V	V	V		V	V	V	307	