

# UTECH Fan UD Series

## QUICK REFERENCE GUIDE

Dimension (mm)	Model	Part No. Terminal Leadwire	Bearing System	Rated Voltage (V)	Freq (Hz)	Air Flow (CFM)	Speed (rpm)	Noise Level (dB-A)	UL/ CUL	TUV	
80x80x25	UD8025A2	UD8025A2PBL	Ball	220/240	50/60	20/22	2650/3000	30/34		■	
	UD8025A1	UD8025A1PBL	Ball	110/120	50/60	20/22	2650/3000	30/34	■		
	UD8025A2	UD8025A2PSL	Sleeve	220/240	50/60	20/22	2550/3000	30/34		■	
	UD8025A1	UD8025A1PSL	Sleeve	110/120	50/60	20/22	2550/3000	30/34	■		
	UD8025A2	UD8025A2HBL	Ball	220/240	50/60	18/20	2600/3000	29/33		■	
	UD8025A1	UD8025A1HBL	Ball	110/120	50/60	18/20	2600/3100	29/33	■		
	UD8025A2	UD8025A2HSL	Sleeve	220/240	50/60	18/20	2400/2800	28/32		■	
	UD8025A1	UD8025A1HSL	Sleeve	110/120	50/60	18/20	2400/2800	28/32	■		
80x80x38	UD8038A2	UD8038A2PBL	Ball	220/240	50/60	29/32	2400/2800	32/37		■	
	UD8038A1	UD8038A1PBL	Ball	110/120	50/60	29/32	2400/2800	32/37	■		
	UD8038A2	UD8038A2PSL	Sleeve	220/240	50/60	29/32	2300/2700	32/37		■	
	UD8038A1	UD8038A1PSL	Sleeve	110/120	50/60	29/32	2300/2700	32/37	■		
	UD8038A2	UD8038A2HBL	Ball	220/240	50/60	26/29	2400/2900	30/35		■	
	UD8038A1	UD8038A1HBL	Ball	110/120	50/60	26/29	2300/2700	30/35	■		
	UD8038A2	UD8038A2HSL	Sleeve	220/240	50/60	26/29	2200/2600	30/35		■	
	UD8038A1	UD8038A1HSL	Sleeve	110/120	50/60	26/29	2200/2600	30/35	■		
	UD8038A2	UD8038A2MBL	Ball	220/240	50/60	22/24	2100/2400	25/28		■	
	UD8038A1	UD8038A1MBL	Ball	110/120	50/60	22/24	2100/2400	25/28	■		
	UD8038A2	UD8038A2MSL	Sleeve	220/240	50/60	21/23	2000/2300	24/27		■	
	UD8038A1	UD8038A1MSL	Sleeve	110/120	50/60	21/23	2000/2300	24/27	■		
	92x92x25	UD9225A2	UD9225A2PBT(L)	Ball	220/240	50/60	33/36	2550/2900	37/39		■
		UD9225A1	UD9225A1PBT(L)	Ball	110/120	50/60	33/36	2550/2900	37/39	■	
UD9225A2		UD9225A2PST(L)	Sleeve	220/240	50/60	33/36	2550/2900	37/39		■	
UD9225A1		UD9225A1PST(L)	Sleeve	110/120	50/60	33/36	2550/2900	37/39	■		
UD9225A2		UD9225A2HBT(L)	Ball	220/240	50/60	29/33	2400/2800	35/37		■	
UD9225A1		UD9225A1HBT(L)	Ball	110/120	50/60	29/33	2400/2800	35/37	■		
UD9225A2		UD9225A2HST(L)	Sleeve	220/240	50/60	29/33	2300/2700	34/36		■	
UD9225A1		UD9225A1HST(L)	Sleeve	110/120	50/60	29/33	2300/2700	34/36	■		
92x92x38	UD9238A2	UD9238A2PBL	Ball	220/240	50/60	50/60	2300/2600	39/43		■	
	UD9238A2	UD9238A2PSL	Sleeve	220/240	50/60	50/60	2300/2600	39/43		■	
	UD9238A2	UD9238A2HBL	Ball	220/240	50/60	45/55	2200/2500	37/41		■	
	UD9238A2	UD9238A2HSL	Sleeve	220/240	50/60	45/55	2200/2500	37/41		■	

Dimension (mm)	Model	Part No. Terminal Lead Wire	Bearing System	Rated Voltage (V)	Freq. (Hz)	Air Flow (CFM)	Speed (rpm)	Noise Level (dB-A)	UL/ CUL	TUV
110x110x25	UD1125A2	UD1125A2PBL	Ball	220/240	50/60	48/55	2300/2400	39/42	■	■
	UD1125A1	UD1125A1PBL	Ball	110/120	50/60	48/55	2300/2400	39/42	■	■
	UD1125A2	UD1125A2PSL	Sleeve	220/240	50/60	48/55	2300/2400	36/39	■	■
	UD1125A1	UD1125A1PSL	Sleeve	110/120	50/60	48/55	2300/2400	36/39	■	■
	UD1125A2	UD1125A2HBL	Ball	220/240	50/60	43/49	2200/2300	37/40	■	■
	UD1125A1	UD1125A1HBL	Ball	110/120	50/60	43/49	2200/2300	37/40	■	■
	UD1125A2	UD1125A2HSL	Sleeve	220/240	50/60	43/49	2200/2300	37/40	■	■
	UD1125A1	UD1125A1HSL	Sleeve	110/120	50/60	43/49	2200/2300	37/40	■	■
120x120x25	UD1225A2	UD1225A2PBL	Ball	220/240	50/60	60/67	2300/2500	38/40	■	■
	UD1225A1	UD1225A1PBL	Ball	110/120	50/60	60/67	2300/2500	38/40	■	■
	UD1225A2	UD1225A2PSL	Sleeve	220/240	50/60	60/67	2300/2500	38/40	■	■
	UD1225A1	UD1225A1PSL	Sleeve	110/120	50/60	60/67	2300/2500	38/40	■	■
	UD1225A2	UD1225A2HBL	Ball	220/240	50/60	56/62	2200/2300	46/48	■	■
	UD1225A1	UD1225A1HBL	Ball	110/120	50/60	56/62	2200/2400	46/48	■	■
	UD1225A2	UD1225A2HSL	Sleeve	220/240	50/60	56/62	2100/2200	46/48	■	■
	UD1225A1	UD1225A1HSL	Sleeve	110/120	50/60	56/62	2100/2300	46/48	■	■
	UD1225A2	UD1225A2MBL	Ball	220/240	50/60	50/53	2100/2200	40/42	■	■
	UD1225A1	UD1225A1MBL	Ball	110/120	50/60	50/53	2100/2200	40/42	■	■
	UD1225A2	UD1225A2MSL	Sleeve	220/240	50/60	50/53	2000/2100	40/42	■	■
	UD1225A1	UD1225A1MSL	Sleeve	110/120	50/60	50/53	2100/2200	40/42	■	■
120x120x38	UD1238A2	UD1238A2PBT(L)	Ball	220/240	50/60	103/108	2600/3100	40/45	■	■
	UD1238A1	UD1238A1PBT(L)	Ball	110/120	50/60	103/108	2600/3100	40/45	■	■
	UD1238A2	UD1238A2PST(L)	Sleeve	220/240	50/60	103/108	2500/3000	38/43	■	■
	UD1238A1	UD1238A1PST(L)	Sleeve	110/120	50/60	103/108	2500/3000	38/43	■	■
	UD1238A2	UD1238A2HBT(L)	Ball	220/240	50/60	86/98	2600/3000	42/47	■	■
	UD1238A1	UD1238A1HBT(L)	Ball	110/120	50/60	86/98	2600/3000	42/47	■	■
	UD1238A2	UD1238A2HST(L)	Sleeve	220/240	50/60	86/98	2500/2900	42/47	■	■
	UD1238A1	UD1238A1HST(L)	Sleeve	110/120	50/60	86/98	2500/2900	42/47	■	■
	UD1238A2	UD1238A2MBT(L)	Ball	220/240	50/60	70/73	2300/1700	33/35	■	■
	UD1238A1	UD1238A1MBT(L)	Ball	110/120	50/60	70/73	2600/2400	33/35	■	■
	UD1238A2	UD1238A2MST(L)	Sleeve	220/240	50/60	70/73	2100/1300	33/35	■	■
	UD1238A1	UD1238A1MST(L)	Sleeve	110/120	50/60	70/73	2300/2200	33/35	■	■
	UD1238A2	UD1238A2LBT(L)	Ball	220/240	50/60	60/62	1800/2000	30/32	■	■
	UD1238A1	UD1238A1LBT(L)	Ball	110/120	50/60	60/62	1800/2000	30/32	■	■
	UD1238A2	UD1238A2LST(L)	Sleeve	220/240	50/60	60/62	1800/2000	30/32	■	■
	UD1238A1	UD1238A1LST(L)	Sleeve	110/120	50/60	60/62	1800/2000	30/32	■	■
172x150x51	UD1725A2	UD1725A2PBT(L)	Ball	220/240	50/60	208/216	2600/2700	61/56	■	■
	UD1725A1	UD1725A1PBT(L)	Ball	110/120	50/60	208/216	2600/3000	61/56	■	■
	UD1725A2	UD1725A2PST(L)	Sleeve	220/240	50/60	208/216	2500/2600	58/53	■	■
	UD1725A1	UD1725A1PST(L)	Sleeve	110/120	50/60	208/216	2500/2900	58/53	■	■
	UD1725A2	UD1725A2HBT(L)	Ball	220/240	50/60	196/208	2600/2700	50/45	■	■
	UD1725A1	UD1725A1HBT(L)	Ball	110/120	50/60	196/208	2600/2700	50/45	■	■
	UD1725A2	UD1725A2HST(L)	Sleeve	220/240	50/60	196/208	2500/2600	48/43	■	■
	UD1725A1	UD1725A1HST(L)	Sleeve	110/120	50/60	196/208	2500/2600	48/43	■	■
	UD1725A2	UD1725A2MBT(L)	Ball	220/240	50/60	145/180	2400/2550	44/41	■	■
	UD1725A1	UD1725A1MBT(L)	Ball	110/120	50/60	145/180	2400/2550	44/41	■	■
	UD1725A2	UD1725A2MST(L)	Sleeve	220/240	50/60	139/174	2350/2500	43/41	■	■
	UD1725A1	UD1725A1MST(L)	Sleeve	110/120	50/60	139/174	2350/2500	43/41	■	■