




# DC Axial Fan

## AT8025L Series

80x80x25mm |



Model	Rated Voltage (VDC)	Operating Voltage (VDC)	Rated Current (AMP)	Power Consumption (WATTS)	Speed Reference (RPM)	AirFlow (CMM) (CFM)		Static Pressure (mm-H2O) (Inch-H2O)		Acoustic Noise (dBA)
AT8025L-05L-S/2B/FB	5	4.0-5.5	0.14	0.70	2000	0.687	24.25	1.51	0.059	24.8
AT8025L-05MS/2B/FB	5	4.0-5.5	0.20	1.00	2500	0.972	34.33	2.24	0.088	31.2
AT8025L-05HS/2B/FB	5	4.0-5.5	0.39	1.95	3000	1.112	39.29	3.36	0.132	35.7
AT8025L-12LS/2B/FB	12	8-13.8	0.10	1.20	2000	0.687	24.25	1.51	0.059	24.8
AT8025L-12MS/2B/FB	12	8-13.8	0.11	1.32	2500	0.972	34.33	2.24	0.088	31.2
AT8025L-12MS/2B/FB	12	8-13.8	0.11	1.32	2500	0.972	34.33	2.24	0.088	31.2
AT8025L-12HS/2B/FB	12	8-13.8	0.17	2.04	3000	1.112	39.29	3.36	0.132	35.7
AT8025L-12HS/2B/FB	12	8-13.8	0.17	2.04	3000	1.112	39.29	3.36	0.132	35.7
AT8025L-12HS/2B/FB	12	8-13.8	0.34	4.08	3500	1.395	49.26	3.95	0.156	39.7
AT8025L-12HHS/2B/FB	12	8-13.8	0.43	5.16	4000	1.681	59.37	5.22	0.206	43.6
AT8025L-12TH2B	12	8-13.8	0.08	1.92	2000	0.687	24.25	1.51	0.059	24.8
AT8025L-24LS/2B/FB	24	12-27.6	0.10	2.40	2500	0.972	34.33	2.24	0.088	31.2
AT8025L-24MS/2B/FB	24	12-27.6	0.11	2.64	3000	1.112	39.29	3.36	0.132	35.7
AT8025L-24MS/2B/FB	24	12-27.6	0.17	4.08	3500	1.395	49.26	3.95	0.156	39.7
AT8025L-24HHS/2B/FB	24	12-27.6	0.29	6.96	4000	1.681	59.37	5.22	0.206	43.6
AT8025L-24TH2B	24	12-27.6	0.08	1.92	2000	0.687	24.25	1.51	0.059	24.8
AT8025L-48MS/2B/FB	48	24-52.8	0.07	3.36	2500	0.972	34.33	2.24	0.088	31.2
AT8025L-48HS/2B/FB	48	24-52.8	0.08	3.84	3000	1.112	39.29	3.36	0.132	35.7



DC Fan

### DC FAN

- Frame & Impeller: Plastic (UL94V-0)
- Bearing: Dual Ball Bearing
- Basic Locked Roter and Polarity Protected
- Safety Standards: UL/CUL, TUV(05V, 48V : Approval Pending)