



DC Axial Fan

AT8025L Series

80x80x25mm IV



Model	Rated Voltage (VDC)	Operating Voltage (VDC)	Rated Current (AMP)	Power Consumption (WATTS)	Speed Reference (RPM)	AirFlow (CMM) (CFM)	Static Pressure (mm-H ₂ O) (inch-H ₂ O)	Acoustic Noise (dBA)
AT8025L-12LS/2B/FB	12	8~13.8	0.07	0.84	1800	0.688 24.29	1.41 0.056	21.3
AT8025L-12MS/2B/FB	12	8~13.8	0.12	1.44	2400	0.923 32.58	2.61 0.103	28.0
AT8025L-12MS/2B/FB	12	8~13.8	0.09	1.08	2400	0.923 32.58	2.61 0.103	28.0
AT8025L-12HS/2B/FB	12	8~13.8	0.19	2.28	3000	1.112 39.25	3.75 0.148	33.1
AT8025L-12HS/2B/FB	12	8~13.8	0.28	3.36	3000	1.112 39.25	3.75 0.148	33.1
AT8025L-12HHS/2B/FB	12	8~13.8	0.26	3.12	3600	1.259 44.46	4.47 0.176	38.0
AT8025L-12HHS/2B/FB	12	8~13.8	0.26	3.12	3600	1.259 44.46	4.47 0.176	38.0
AT8025L-12TH2B-	12	8~13.8	0.50	6.00	4200	1.541 54.43	7.06 0.278	41.3
AT8025L-24LS/2B/FB	24	12~27.6	0.06	1.34	1800	0.688 24.29	1.41 0.056	21.3
AT8025L-24MS/2B/FB	24	12~27.6	0.09	2.16	2400	0.923 32.58	2.61 0.103	28.0
AT8025L-24HS/2B/FB	24	12~27.6	0.12	2.88	3000	1.112 39.25	3.75 0.148	33.1
AT8025L-24HHS/2B/FB	24	12~27.6	0.20	4.80	3600	1.259 44.46	4.47 0.176	38.0
AT8025L-24TH2B-	24	12~27.6	0.22	5.28	4200	1.541 54.43	7.06 0.278	41.3
AT8025L-24FH2B-	24	12~27.6	0.50	12.00	4800	1.763 62.25	9.99 0.393	44.4



DC Fan

DC FAN

- Frame & Impeller: Plastic (UL94V-0)
- Bearing: Dual Ball Bearing
- Basic Locked Roter and Polarity Protected
- Safety Standards: UL/CUL, TUV