


## 120x120x38mm

### AC Fan



Frame : Aluminum painted & Plastic (UL94V-O)  
 Impeller: Plastic (UL94V-O P.B.T.)  
 Bearing: Ball Bearing & Sleeve Bearing  
 Safety Standards: UL/CUL, TUV

Model	Part No. Terminal Leadwire	Bearing System	Rated Voltage (V)	Freq (Hz)	Current (A)	Input Power (W)	Speed (rpm)	Air Flow (CFM)	Static Pressure (mm-H <sub>2</sub> O)	Noise Level (dB-A)	Weight (g)
UT1238HA1	1238HA1SAT(L)	Sleeve	110/120	50/60	0.21/0.09	16/25	2600/3000	84/100	0.28/0.34	45/51	520
	1238HA1BAT(L)	Ball									
UT1238HA2	1238HA2SAT(L)	Sleeve	220/240	50/60	0.09/0.12	15/22	2600/3000	84/100	0.28/0.34	45/51	520
	1238HA2BAT(L)	Ball									
UT1238MA1	1238MA1SAT(L)	Sleeve	110/120	50/60	0.13/0.17	10/14	2500/2800	80/90	0.18/0.24	39/43	520
	1238MA1BAT(L)	Ball									
UT1238MA2	1238MA2SAT(L)	Sleeve	220/240	50/60	0.07/0.09	11/16	2500/2800	80/90	0.18/0.24	39/43	520
	1238MA2BAT(L)	Ball									
UT1238LA1	1238LA1SAT(L)	Sleeve	110/120	50/60	0.10/0.12	9/11	1900/2500	65/78	0.10/0.18	35/40	520
	1238LA1BAT(L)	Ball									
UT1238LA2	1238LA2SAT(L)	Sleeve	220/240	50/60	0.05/0.06	9/11	1900/2500	65/78	0.10/0.18	35/40	520
	1238LA2BAT(L)	Ball									

