



## 92x92x25 mm

### AC Fan

Frame : Aluminum painted & Plastic (UL94V-O)  
 Impeller: Plastic (UL94V-O P.B.T.)  
 Bearing: Ball Bearing & Sleeve Bearing  
 Safety Standards: UL/CUL, TUV



9225



92025

| Model      | Part No.<br>Terminal<br>Leadwire | Bearing<br>System | Rated<br>Voltage<br>(V) | Freq<br>(Hz) | Current<br>(A) | Input<br>Power<br>(W) | Speed<br>(rpm) | Air Flow<br>(CFM) | Static<br>Pressure<br>(mm-H2O) | Noise<br>Level<br>(dB-A) | Weight<br>(g) |
|------------|----------------------------------|-------------------|-------------------------|--------------|----------------|-----------------------|----------------|-------------------|--------------------------------|--------------------------|---------------|
| UT9225HA1  | 9225HA1SAT(L)                    | Sleeve            | 110/120                 | 50/60        | 0.20/0.21      | 19/17                 | 1700/2200      | 30/36             | 0.16/0.20                      | 35/37                    | 230           |
|            | 9225HA1BAT(L)                    | Ball              |                         |              |                |                       |                |                   |                                |                          |               |
| UT9225HA2  | 9225HA2SAT(L)                    | Sleeve            | 220/240                 | 50/60        | 0.09/0.10      | 19/17                 | 1700/2200      | 30/36             | 0.16/0.20                      | 35/37                    | 230           |
|            | 9225HA2BAT(L)                    | Ball              |                         |              |                |                       |                |                   |                                |                          |               |
| UT92025HA1 | 92025HA1SAT(L)                   | Sleeve            | 110/120                 | 50/60        | 0.12/0.14      | 10/15                 | 2300/2800      | 40/48             | 0.18/0.22                      | 35/37                    | 230           |
|            | 92025HA1BAT(L)                   | Ball              |                         |              |                |                       |                |                   |                                |                          |               |
| UT92025HA2 | 92025HA2SAT(L)                   | Sleeve            | 220/240                 | 50/60        | 0.05/0.06      | 10/15                 | 2300/2800      | 40/48             | 0.18/0.22                      | 35/37                    | 230           |
|            | 92025HA2BAT(L)                   | Ball              |                         |              |                |                       |                |                   |                                |                          |               |

