

UT Series AC Fan

QUICK REFERENCE GUIDE

Dimension (mm)	Model	Part No. Terminal Leadwire	Bearing System	Rated Voltage (V)	Freg (Hz)	Air Flow (CFM)	Speed (rpm)	Noise Level (dB-A)	UL/ CUL	TUV
Ø250 X 89	UT2509HA1	2509HA1BAT(L)	Ball	110/120	50/60	510/600	1450/1850	48/56	■	
	UT2509HA2	2509HA2BAT(L)	Ball	220/240	50/60	510/600	1450/1850	48/56	■	■
172 X 150 X 51	UT1725HA1	1725HA1SAT(L)	Sleeve	110/120	50/60	190/220	2700/3100	53/59	■	
		1725HA1BAT(L)	Ball	110/120	50/60	190/220	2700/3100	53/59	■	■
	UT1725HA2	1725HA2SAT(L)	Sleeve	220/240	50/60	190/220	2700/3100	53/59	■	
		1725HA2BAT(L)	Ball	220/240	50/60	190/220	2700/3100	53/59	■	■
172 X 152 X 38	UT1723HA1	1723HA1BAT(L)	Ball	110/120	50/60	110/120	2600/3000	48/53	■	■
	UT1723HA2	1723HA2BAT(L)	Ball	220/240	50/60	220/240	2600/3000	48/53	■	■
Ø150 X 38	UT1538HA1	1538HA1SAT(L)	Sleeve	110/120	50/60	72/85	2600/3000	45/50	■	■
		1538HA1BAT(L)	Ball	110/120	50/60	72/85	2600/3000	45/50	■	■
	UT1538HA2	1538HA2SAT(L)	Sleeve	220/240	50/60	72/85	2600/3000	45/50	■	
		1538HA2BAT(L)	Ball	220/240	50/60	72/85	2600/3000	45/50	■	
120 X 120 X 38	UT1238HA1	1238HA1SAT(L)	Sleeve	110/120	50/60	84/100	2600/3000	45/51	■	
		1238HA1BAT(L)	Ball	110/120	50/60	84/100	2600/3000	45/51	■	
	UT1238HA2	1238HA2SAT(L)	Sleeve	220/240	50/60	84/100	2600/3000	45/51	■	■
		1238HA2BAT(L)	Ball	220/240	50/60	84/100	2600/3000	45/51	■	■
	UT1238MA1	1238MA1SAT(L)	Sleeve	110/120	50/60	80/90	2500/2800	39/43	■	
		1238MA1BAT(L)	Ball	110/120	50/60	80/90	2500/2800	39/43	■	
	UT1238MA2	1238MA2SAT(L)	Sleeve	220/240	50/60	80/90	2500/2800	39/43	■	■
		1238MA2BAT(L)	Ball	220/240	50/60	80/90	2500/2800	39/43	■	■
	UT1238LA1	1238LA1SAT(L)	Sleeve	110/120	50/60	65/78	1900/2500	35/40	■	
		1238LA1BAT(L)	Ball	110/120	50/60	65/78	1900/2500	35/40	■	
	UT1238LA2	1238LA2SAT(L)	Sleeve	220/240	50/60	65/78	1900/2500	35/40	■	■
		1238LA2BAT(L)	Ball	220/240	50/60	65/78	1900/2500	35/40	■	■
120 X 120 X 38 Dual Voltage	UT1238HA1/A2	1238HA1SAT(L)	Sleeve	110/240	50/60	84/100	2600/3000	45/51	■	
		1238HA1BAT(L)	Ball	110/240	50/60	84/100	2600/3000	45/51	■	
120 X 120 X 38 24 Volyage	UT1238HA24	1238HA24SAT(L)	Sleeve	24	50/60	85/93	2600/2900	36/40		
		1238HA24BAT(L)	Ball	24	50/60	85/93	2600/2900	36/40		

Dimension (mm)	Model	Part No. Terminal Leadwire	Bearing System	Rated Voltage (V)	Freg (Hz)	Air Flow (CFM)	Speed (rpm)	Noise Level (dB-A)	UL/ CUL	TUV	
120 X 120 X 25	UT1225HA1	1225HA1SAT(L)	Sleeve	110/120	50/60	60/76	1900/2500	40/44	■		
		1225HA1BAT(L)	Ball	110/120	50/60	60/76	2000/2500	40/44	■	■	
	UT1225HA2	1225HA2SAT(L)	Sleeve	220/240	50/60	60/76	1900/2500	40/44	■		
		1225HA2BAT(L)	Ball	220/240	50/60	60/76	2000/2500	40/44	■	■	
	UT1225LA1	1225LA1SAT(L)	Sleeve	110/120	50/60	50/60	1900/2500	33/37	■		
		1225LA1BAT(L)	Ball	110/120	50/60	50/60	2000/2500	33/37	■	■	
	UT1225LA2	1225LA2SAT(L)	Sleeve	220/240	50/60	50/60	1900/2500	33/37	■		
		1225LA2BAT(L)	Ball	220/240	50/60	50/60	2000/2500	33/37	■	■	
	92 X 92 X 38	UT9238HA1	9238HA1SAT(L)	Sleeve	110/120	50/60	45/55	2200/2600	37/41	■	■
			9238HA1BAT(L)	Ball	110/120	50/60	45/55	2200/2600	37/41	■	■
		UT9238HA2	9238HA2SAT(L)	Sleeve	220/240	50/60	45/55	2200/2600	37/41	■	
			9238HA2BAT(L)	Ball	220/240	50/60	45/55	2200/2600	37/41	■	
92 X 92 X 25	UT9225HA1	9225HA1SAT(L)	Sleeve	110/120	50/60	30/36	1700/2200	35/37	■	■	
		9225HA1BAT(L)	Ball	110/120	50/60	30/36	1700/2200	35/37	■	■	
	UT9225HA2	9225HA2SAT(L)	Sleeve	220/240	50/60	30/36	1700/2200	35/37	■		
		9225HA2BAT(L)	Ball	220/240	50/60	30/36	1700/2200	35/37	■		
	UT92025HA1	92025HA1SAT(L)	Sleeve	110/120	50/60	40/48	2300/2800	35/37	■	■	
		92025HA1BAT(L)	Ball	110/120	50/60	40/48	2300/2800	35/37	■	■	
	UT92025HA2	92025HA2SAT(L)	Sleeve	220/240	50/60	40/48	2300/2800	35/37	■		
		92025HA2BAT(L)	Ball	220/240	50/60	40/48	2300/2800	35/37	■		
80 X 80 X 38	UT8038HA1	8038HA1SAT(L)	Sleeve	110/120	50/60	32/35	2300/2800	35/31	■	■	
		8038HA1BAT(L)	Ball	110/120	50/60	32/35	2300/2800	35/31	■	■	
	UT8038HA2	8038HA2SAT(L)	Sleeve	220/240	50/60	32/35	2300/2800	35/31	■		
		8038HA2BAT(L)	Ball	220/240	50/60	32/35	2300/2800	35/31	■		
80 X 80 X 25	UT8025HA1	8025HA1SAL	Sleeve	110/120	50/60	21/23	1700/2200	29/33	■		
		8025HA1BAL	Ball	110/120	50/60	21/23	1700/2200	29/33	■		
	UT8025HA2	8025HA2SAL	Sleeve	220/240	50/60	21/23	1700/2200	29/33	■	■	
		8025HA2BAL	Ball	220/240	50/60	21/23	1700/2200	29/33	■	■	
	UT80025HA1	80025HA1SAL	Sleeve	110/120	50/60	26/33	2300/2800	29/33	■		
		80025HA1BAL	Ball	110/120	50/60	26/33	2300/2800	29/33	■		
	UT80025HA2	80025HA2SAL	Sleeve	220/240	50/60	26/33	2300/2800	29/33	■	■	
		80025HA2BAL	Ball	220/240	50/60	26/33	2300/2800	29/33	■	■	